



Transfer Switches						
Model Number		71130	71230	71132	71212	71232
Frequency, Hz		60	60	60	60	60
Voltage, VAC		120 / 240	120 / 240	120 / 240	120 / 240	120 / 240
Amps, A		100	200	100	100	200
Phase		Single	Single	Single	Single	Single
Poles		2	2	2	2	2
Power Management		No	No	Symphony® II	No	Symphony® II
Enclosure Type		3R	3R	3R	3R	3R
SED Rated		Yes	Yes	Yes	No	Yes
Utility Breaker, A		100	200	100	N/A	200
Load Transition Type (Automatic)		Open Transition	Open Transition	Open Transition	Open Transition	Open Transition
UL Listing		1008	1008	1008	1008	1008
Withstand Rating (RMS Symmetrical Amps)		22,000	25,000	22,000	5000 w/o breaker / 22,000 w/ breaker	25,000
Lug Range	Utility:	14AWG - 1/0	2AWG - 300MCM	14AWG - 1/0	14AWG - 1/0	2AWG - 300MCM
	Generator:	14AWG - 1/0	6AWG - 250MCM	14AWG - 1/0	14AWG - 1/0	6AWG - 250MCM
	Load:	14AWG - 1/0	6AWG - 250MCM	14AWG - 1/0	14AWG - 1/0	6AWG - 250MCM
Enclosure Size, Centimeters Length x Width x Depth		61 x 35.6 x 15.2	76.2 x 40.6 x 17.8	61 x 35.6 x 15.2	61 x 35.6 x 15.2	61 x 35.6 x 15.2
Wire-Whip		No	No	No	6575 (Acc, Kit)	No
Limited Warranty*		5 Years	5 Years	6 Years	5 Years	6 Years

**Shared Specifications of Transfer Switches**

<b>Type</b>	Open Transition
<b>Poles</b>	2 per Switch
<b>Application</b>	Single Phase
<b>Rated Voltage</b>	240 Volts
<b>Frequency</b>	60 Hz
<b>Enclosure</b>	Powder Coated Galvanneal
<b>Rating</b>	NEMA 3R
<b>Color</b>	Gray

**Transfer Switch Operations & Settings**

<b>Utility Voltage Drop-Out</b>	<70%
<b>Time for Generator to Start</b>	6 Second Factory Set
<b>Engine Warm-Up Delay</b>	20 or 50 Seconds
<b>Utility Voltage Pickup</b>	>80%
<b>Managed Loads Delay</b>	5 Minutes After Transfer
<b>Re-Transfer Delay</b>	10 Seconds
<b>Cool-Down Timer</b>	60 Seconds
<b>Exerciser (Controlled by Generator)</b>	20 Minutes Every 7 Days

**Symphony® II PLC Modules**

Type	Line Voltage	Low Voltage	Dual Low Voltage
<b>Model Number</b>	71051	71052	71053
<b>Amperage</b>	50		
<b>Voltage</b>	240 V	120 V	120 V
<b>Frequency</b>	60 Hz	60 Hz	60 Hz
<b>Application</b>	Any 120 Volt Circuit	Thermostatically Controlled Appliances	Thermostatically Controlled Appliances
<b>Examples</b>	Stove, Dryer, Pump	Air Conditioner	Air Conditioners, Heat Pump, Strip Heat
<b>Enclosure Rating</b>	NEMA 4	NEMA 4	NEMA 4
<b>Color</b>	Gray	Gray	Gray
<b>Enclosure Material</b>	Plastic	Plastic	Plastic
<b>Limited Warranty*</b>	3 Years	3 Years	3 Years
<b>Dimensions, Centimeters</b>	22.2 x 14 x 7.6 (22.2 x 15.2 x 7.6 Including Mounting Legs)	22.2 x 14 x 7.6 (22.2 x 15.2 x 7.6 Including Mounting Legs)	22.2 x 14 x 7.6 (22.2 x 15.2 x 7.6 Including Mounting Legs)
<b>Weight</b>	4.4 lbs	2 lbs	2.1 lbs
<b>Wiring Size</b>	8	18	18
<b>UL Listed</b>	Yes	Yes	Yes
<b>Communication</b>	Symphony® II PLC	Symphony® II PLC	Symphony® II PLC

**Amplify™ Modules**

Type	High Voltage	Dual Low Voltage
<b>Model Number</b>	6537	6536
<b>Amperage</b>	50	
<b>Voltage</b>	240 V	240 V
<b>Frequency</b>	60 Hz	60 Hz
<b>Application</b>	Any 240 Volt Circuit	Thermostatically Controlled Appliances
<b>Examples</b>	Stove, Dryer, Pump	Air Conditioners, Heat Pump, Strip Heat
<b>Enclosure Rating</b>	NEMA 4	NEMA 4
<b>Color</b>	Gray	Gray
<b>Enclosure Material</b>	Plastic	Plastic
<b>Limited Warranty*</b>	3 Years	3 Years
<b>Dimensions, Centimeters</b>	22.2 x 14 x 7.6 (22.2 x 15.2 x 7.6 Including Mounting Legs)	22.2 x 14 x 7.6 (22.2 x 15.2 x 7.6 Including Mounting Legs)
<b>Weight</b>	4.4 lbs	2.1 lbs
<b>Wiring Size</b>	8	18
<b>UL Listed</b>	Yes	Yes
<b>Communication</b>	Zigbee	Zigbee

\* See operator's manual or [www.briggsandstratton.com](http://www.briggsandstratton.com) for complete warranty details.

Review local codes to determine if a transfer switch with separate service entrance disconnect is required.

Briggs & Stratton reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation.

BS1222 - 03/20

**BRIGGS & STRATTON CORPORATION**  
Post Office Box 702  
Milwaukee, WI 53201-0702 USA  
Copyright ©2020. All rights reserved.

